

ELECTRONIC speed controllers



Electronic speed controller REB range

The REB range of electronic speed controller is for use in general areas. The casing is protected to class IP44.

Mains Supply: 230V~ 50 / 60Hz

Output: Variable - 3 wire speed control recommended for best results

Technical details and dimensions:

Model/Code	Max. Current (A)	Dimensions (mm)			IP Rating
		Width	Length	Depth	
REB-1	1A	120	100	55	IP42
REB-3	3A	120	100	55	IP42
REB-5	5A	148	88	55	IP42
REB-6	6A	148	88	55	IP42
REB-8	8A	95	145	70	IP42
REB-10	10A	127	205	95	IP42
REB-12	12A	222	146	60	IP42
REB-16	16A	222	146	83	IP42

DIRECT ON LINE (DOL) starter range

The DOL range of Direct On Line Starters is fitted with a current overload relay and is suitable for use in most Commercial and Industrial areas.

Mains Supply: DOL 1-10A and DOL 1-16A 230V ~ 50Hz
DOL 3-9A and DOL 3-16A 400V ~ 50Hz

Technical details:

Model/Code

DOL 1-10A

DOL 1-16A

DOL 3-9A

DOL 3-16A

Current Overload Relays ratings:

1.0 - 1.6 A

1.6 - 2.5 A

2.5 - 4.0 A

4.0 - 6.5 A

6.3 - 10.0 A

9.0 - 14.0 A

Please note: Other values of current overload relay are available upon request

Please specify current overload required when ordering the DoL Starter. (See overload ratings available below)

