


Product 1150 HQD 355/4 EX

Image



Characteristics



Air flow volume m³/h

Properties

Ref.no.	1150 - 021								
Model	HQD 355/4 EX								
Description	High efficiency axial fan 3-ph., explosion proof with safety guard guard								
Actual pressure	static								
Actual volume									
Max.Vol.	3060 m³/h								
Speed	1400 min-1								
FLC un-controlled	0.41 A								
STC un-controlled	1.23 A								
Power	0.12 kW								
Voltage	400 V / 3 ph / 50 Hz								
Max.temp.	40 °C								
Wiring diagram no.	470								
Weight	9.50 kg								
Delivery time	Ex stock								
Acoustic data:									
Sound in-duct	55 in 4 m								
Case breakout									
Intake	Hz	Total	125	250	500	1k	2k	4k	8k
Lwa Intake	dB(A)	75	61	65	72	69	67	61	52
Lwa Extract	dB(A)	0	0	0	0	0	0	0	0
Lwa Breakout	dB(A)	0	0	0	0	0	0	0	0

Description

HQD 355/4 EX

High efficiency axial fan
3-ph., explosion proof
with safety guard guard

Square plate high efficiency axial fan with inlet cone, directly driven, explosion proof according to ATEX.

Square mounting plate with drawn bell mouth inlet in galvanised sheet-steel.


Highly efficient axial impeller with 5 blades from impact resistant polymers. Dynamically balanced (Class G 6.3 to VDI 2060 and DIN ISO 1940). Suitable for -30°C to +40°C. Electrical resistance of less than 1 GOhm.

Totally enclosed, maintenance free 3-phase squirrel cage motor, low noise sealed for life ball bearings, not controllable. Explosion proof execution according to ATEX.

Accessories

Image	Ref.no.	Model	Description	Group
	808	F 355	ADAPTION PLATE FOR GRILLE	A
	753	RAG 355	RAIN-REPELLENT GRILLE	A
	1594	RHS 3+1	Isolator switch 3 pole isolator with additional terminal, 400V	A
	769	RVK 355	MANUAL GRILLE	A
	761	VK 355	GRAVITY OPERATED SHUTTER MADE FROM POLYMERS	A

Wiring diagram



Dimensions