


Product 1467 HQD 450/4/4

Image



Characteristics



Properties

Ref.no.	1467 - 020
Model	HQD 450/4/4
Description	High efficiency axial fan 3-ph., 2 speed, Y/?- motor with safety guard guard
Actual pressure	static
Actual volume	
Max.Vol.	5780 m³/h
Speed	1128 / 1389 min-1
FLC un-controlled	0.51 / 0.82 A
STC un-controlled	3.28 A
Power	0.28 / 0.3780 kW
Voltage	400 / 400 V / 3 ph / 50 Hz
Max.temp.	60 °C
Wiring diagram no.	520
Weight	22.00 kg
Delivery time	On request
Acoustic data:	
Sound in-duct	62 in 4 m
Case breakout	
Intake	Hz
Lwa Intake	dB(A)
Lwa Extract	dB(A)
Lwa Breakout	dB(A)

Total	125	250	500	1k	2k	4k	8k
82	68	72	79	76	74	68	60
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0

Description

HQD 450/4/4

High efficiency axial fan
3-ph., 2 speed, Y/?- motor
with safety guard guard

Square plate high efficiency axial fan with inlet cone, directly driven.

Square mounting plate with drawn bell mouth inlet and duct in galvanised sheet-steel and finished with two coats of paint.


Highly efficient, profiled blade impeller from polymers, aerodynamically optimised to the application, dynamically balanced. Suitable for -30 °C to +60 °C.

Totally enclosed, 3-phase squirrel cage motor, 2-speed star/delta switching. Maintenance free, low-noise sealed for life ball bearings.

Accessories

Image	Ref.no.	Model	Description	Group
	1351	DS 2	STAR / DELTA SWITCH 400 V, 3-PH., MAX 12 A, IP 65 400 V, 3-PH., MAX 12 A, IP 65	A
	779	EVK 450	ELECTRICAL LOUVRE GRILLES CONTROL VIA RELAY (BY OTHERS)	A
	810	F 450	ADAPTION PLATE FOR GRILLE	A
	5459	FU-BS 2,5	Frequency inverter Basic Sinus 400V 3PH 50/60HZ 2,5A	R
	Additional part to product 5459:			
	1437	EDR	Electronic pressure controller for EC and AC fans with FU 24V / 0-10V	A
	1438	ETR	Electronic temperature controller for EC and AC fans with FU 24V / 0-10V	A
	1322	LDF 500	PRESSURE SENSOR FOR EUR 6, 0-500 PA MESSBEREICH 0-500 PA	A
	1325	LGF 10	AIR FLOW SPEED SENSOR FOR EUR 6	A
	1336	LTA 40	Outdoor temperature sensor to EUR 6 Temperature range: -20 to +60 °C	A
	1324	LTK 40	DUCT TEMPERATURE SENSOR FOR EUR 6	A
	1323	LTR 40	ROOM TEMPERATURE SENSOR FOR EUR 6	A
	1737	PA 24	Speed potentiometer with operating status signal 24V DC, surface installation	E
	1736	PU 24	Speed potentiometer with LED-light ring 24V DC, flush mounted	E
	4267	SA-3 10	Three step switch surface mounted version	E
	4266	SU-3 10	Three step switch flush mounted version	E
	9990	WSUP	WEEKLY AUTOTIMER WITH POTENTIAL-FREE CHANGEOVER	A
	9577	WSUP-S	AXIAL-HOCHLEISTUNGSVENTILATOR	A
	1571	M 4	FULL MOTOR PROTECTION UNIT FOR 3 PH STAR /DELTA MOTORS WITH DAHLANDER WINDINGS	A
	755	RAG 450	RAIN-REPELLENT GRILLE	A
	1315	RDS 2	5 STEP TRANSFORMER CONTROLLER 3 PH, 400 V, 2.0 A WITH MOTOR PROTECTION UNIT	R
	1595	RHS 6+2	ISOLATOR SWITCH 6-POLE, 230-500 V, 25 A, IP 65 IP 65	A
	771	RVK 450	MANUAL GRILLE	A
	763	VK 450	GRAVITY OPERATED SHUTTER MADE FROM POLYMERS	A
	1271	WS	UNIVERSAL SWITCH FOR 1 + 3 PH	A

Wiring diagram



Dimensions

