


Item: 7176 RDW 200/2
image



Curve graphics



characteristics

item number	7176-001
Article Type	RDW 200/2
Article	Radial roof fan, 1-PH horizontal, 230 V, 2-pole
Is pressure	static
Is volume	
Max.Volumen	1070 m³ / h
rotational speed	2430 min-1
Electricity unregulated	0.56 / 0.56 A
Starting current unregulated	0.952 A.
power	0.1250 kW
tension	230 V / 1 ph / 50 Hz
Max. Temperature	70 ° C (70 ° C if regulated)
Anschlußschemanr.	923
Weight	7.50 kg
delivery time	On demand
Noise data:	
air noise	48 at 4 m
case breakout	51 at 4 m
sound spectrum Hz	Ges. 125 250 500 1k 2k 4k 8k
lwa suction dB (A)	68 44 57 61 63 60 60 57
lwa pressure side dB (A)	71 45 62 66 65 62 62 58
lwa radiation dB (A)	

description

RDW 200/2

Radial roof fan, 1-PH

horizontal, 230 V, 2-pole

Horizontal exhaust roof fan with efficiency-optimized aluminum housing and newly developed high-performance radial impeller.

Housing made of seawater-resistant aluminum with integrated intrusion protection. Motor support plate and base plate with inflow nozzle made of galvanized steel. Base plate with threaded screws for attaching suction-side accessories (hole pattern according to DIN 24155, sheet 3). Protective grille as standard on the discharge side in accordance with DIN EN ISO 13857.

High-performance radial impeller with backward-curved blades made of galvanized sheet steel. Dynamically balanced according to DIN ISO 1940-1.


Speed-controllable single-phase AC external rotor motor in a closed design in IP44. Ball bearing with moisture protection insulation.

Maintenance and radio interference free.


As standard with external terminal box with protection class IP 65.

equipment

image	Item No.	grade	description	WG
	2591	RVS 225 / DRVS 200	Pipe closure flap automatically, with spring	A
	238	ESA 1	AP speed controller, stepless 1-PH, I max. 1 A, 230 V	R
	236	ESU 1	UP speed controller, stepless 1-PH, I max. 1 A, 230 V	R
	1378	FDS 200/225	Flachdachsockel aus GFK mit Klappmechanismus	F
	1201	FR 225 / DFR 200	Winkel-Flanschring	A
	7493	HDH 200	Dachlüftungshaube horizontal	F
	7536	RS 3+1+2 7,5	Revisionsschalter, 5-polig 7,5 kW AC-23B, 400V, 3-PH IP 65, Verriegelung in 0	A
	2575	RVM 225/DRVM 200	Rohr-Verschlußklappe motorbetätigt	A
	5290	SSD 200/225	Sockelschalldämpfer mit Scharnier	F
	1218	STS 225/DSTS 200	Flexible Verbindung mit 2 Rohrflanschen	A
	6520	TSSW 1,5	Drehzahl-Steuertrafo 1-PH 230V 1,5 A, für Schaltschrankeinbau	A
	1495	TSW 1,5	Trafo-Drehzahlsteller 1-PH, 230 V, 1,5 A	R
	1560	WDS 200/225	Welldachsockel	F

Schaltplan

85075 001 SS-923 30.05.08

Maße

LV-Text

RDW 200/2

Horizontal ausblasender Dachventilator mit wirkungsgradoptimiertem Aluminiumgehäuse und neu entwickeltem Hochleistungs-Radiallaufrad. Gehäuse aus seewasserbeständigem Aluminium mit integriertem Eingriffsschutz. Motortragplatte und Grundplatte mit Einströmdüse aus verzinktem Stahl. Grundplatte mit Gewindeschraube zum Befestigen von saugseitigem Zubehör (Lochbild nach DIN 24155, Bl. 3). Schutzgitter serienmäßig an der Ausblasseite entsprechend DIN EN ISO 13857. Hochleistungs-Radial-Laufrad mit rückwärts gekrümmten Schaufeln aus verzinktem Stahlblech. Dynamisch gewuchtet nach DIN ISO 1940-1. "Drehzahlsteuerbarer Einphasen-Wechselstrom-Außenläufermotor in geschlossener Bauart in IP44. Kugelgelagert mit Feuchteschutzisolation. Wartungs- und funkstörungsfrei."

Vol.str. bei 0 Pa	1070	m3/h
Max. Druckerhöhung	485	Pa
Fördermitteldichte	1.2	Kg/m3
Fördermitteltemperatur	70	GradC
Drehzahl	2430	1/min
aufgen. Leistung	0,125	kW
Gewicht	7,5	kg
Ausblasseitig:		
Schalleistung	71	dB(A)
Schalldruck in 4m	54	dB(A)
Spannung	230	Volt
Stromaufnahme	0,56 / 0,56	Amp
Wechselstrom/Drehstrom	W	
Frequenz	50	Hz
Isolierklasse	F	
Schutzart	IP 44	

Make: Helios

Item No .: 7176

Type: RDW 200/2