

RAG



■ Rain repellent grille RAG

To cover intake and exhaust air openings in facades, made of polymer.

- Attractive, corrosion and weather resistant finish in light grey colour prevents rain, snow and insects from entering the system.
- Frame with louvers made of UVresistant, impact resistant polymer. Mesh guard made of galvanised steel and coated with polymer. Mesh size 8 mm.
- Simple (also available as surface mounted or integrated in cladding) installation via dowels (mounting materials included). With adapter F (accessory) also suitable for circular ducting.

WSG



■ Weather proof grille WSG

In square or rectangular landscape format; to cover intake or exhaust air openings in facades.


- Attractive finish protecting against rain, snow and vermin from entering the ducting. Suitable for square, rectangular and circular ducts.
- Solid construction made of aluminium extrusion profile, natural colour, anodised.
- Installation: Flush mounted or integrated in cladding.
- Fixed louvers and mesh guard behind made of galvanised steel. Mesh size: 16 mm.

■ The rectangular models

fit the Helios rectangular fan range and therefore can be fitted to rectangular ducting.

Type	Ref. no.	to fan nominal size mm	Dimensions in mm				Weight kg
			□ B	C	D	E	
RAG 200	0750	180/200	240	28	193	167	0,35
RAG 250	0751	225/250	290	28	243	217	0,45
RAG 315	0752	280/315	340	28	293	267	0,60
RAG 355	0753	355	390	28	343	317	0,75
RAG 400	0754	400	440	28	393	367	1,00
RAG 450	0755	450	490	30	443	417	1,35
RAG 500	0756	500	540	30	493	467	1,60

Type	Ref. no.	Fits to fan nom. size	spigot in mm	Dim. in mm		Weight kg
				□ b	□ B	
WSG 200	0117	180/200	□ 200	195	271	0,8
WSG 250	0118	225/250	□ 250	245	321	1,0
WSG 315	0119	280/315	□ 315	310	386	1,5
WSG 355	0120	355	□ 355	350	426	2,0
WSG 400	0121	400	□ 400	395	471	2,5
WSG 450	0122	450	□ 450	445	521	3,0
WSG 500	0123	500	□ 500	495	571	3,5
WSG 630	0124	600/630	□ 630	625	701	4,0
WSG 710	0125	710	□ 710	705	781	4,5



Type	Ref. no.	Fits to nominal size duct in mm	b	Dim. in mm			Weight kg
				B	h	H	
WSG 30/15	0108	300 x 150	296	370	146	220	0,9
WSG 40/20	0109	400 x 200	396	470	196	270	1,2
WSG 50/25	0110	500 x 250	496	570	246	320	1,9
WSG 50/30	0111	500 x 300	496	570	296	370	2,0
WSG 60/30	0112	600 x 300	596	670	296	370	2,2
WSG 60/35	0113	600 x 350	596	670	346	420	2,4
WSG 70/40	0114	700 x 400	696	770	396	470	2,9
WSG 80/50	0115	800 x 500	796	870	496	570	4,0
WSG 100/50	0116	1000 x 500	996	1070	496	570	5,0

