




ARO BRIDA COMPACT

Circular duct matching flange.
For installation with the COMPACT
TCBB-TCBT and TTT ranges of in-line
cased axial fans.


Model	Ø A	B	Ø C	Ø D	Ø E	N Nº of holes
ARO BRIDA COMPACT-250	323	55	292	250	10	4
ARO BRIDA COMPACT-315	386	55	355	315	10	8
ARO BRIDA COMPACT-355	426	55	395	355	10	8
ARO BRIDA COMPACT-400	487	55	450	400	12	8
ARO BRIDA COMPACT-450	537	55	500	450	12	8
ARO BRIDA COMPACT-500	595	55	560	500	12	12
ARO BRIDA COMPACT-560	655	55	620	560	12	12
ARO BRIDA COMPACT-630	725	55	690	630	12	12
ARO BRIDA COMPACT-710	806	60	770	710	12	16
ARO BRIDA COMPACT-800	896	60	860	800	12	16



ARO BRIDA TGT/THGT N

Circular duct matching flange.
For the installation with THGT and TGT
ranges of in-line cased axial fans.

Model	Ø A	B	Ø C	Ø D	Ø E	Nº of holes	Weight (kg)
ARO BRIDA TGT/THGT-400 N	487	55	450	400	12	8	1,94
ARO BRIDA TGT/THGT-450 N	537	55	500	450	12	8	2,17
ARO BRIDA TGT/THGT-500 N	595	55	560	500	12	12	2,51
ARO BRIDA TGT/THGT-560 N	655	55	620	560	12	12	2,80
ARO BRIDA TGT/THGT-630 N	725	55	690	630	12	12	3,14
ARO BRIDA TGT/THGT-710 N	806	60	770	710	12	16	4,62
ARO BRIDA TGT/THGT-800 N	896	60	860	800	12	16	5,20
ARO BRIDA TGT/THGT-900 N	1006	60	970	900	12	16	6,12
ARO BRIDA TGT/THGT-1000 N	1105	60	1070	1000	15	16	8,00
ARO BRIDA TGT/THGT-1120 N	1225	65	1190	1120	15	20	9,40
ARO BRIDA TGT/THGT-1250 N	1355	65	1320	1250	15	20	10,47
ARO BRIDA TGT/THGT-1400 N	1508	65	1470	1400	15	20	11,88
ARO BRIDA TGT/THGT-1600 N	1725	65	1680	1600	19	24	14,60



IBR

Rectangular duct flange

Model	A	B	C	D	E	F
IBR-200	198	220	240	400	420	440
IBR-225	248	270	290	500	520	540
IBR-250	298	320	340	500	520	540
IBR-285	298	320	340	600	620	640
IBR-315	348	370	390	600	620	640
IBR-355	398	420	440	700	720	740
IBR-400	498	520	540	800	820	840
IBR-450	498	520	540	1000	1020	1040

