


MPC 710 D6 T40

150945


ruck

- Backward curved radial impeller
- Removable side walls, variable discharge direction
- Sheet steel housing double-walled, 30 mm mineral wool
- IE3 motor outside the airflow, controllable
- Conveyed medium temperature up to 120 °C in continuous operation
- Housing bottom designed with integrated drain



MAP

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



zur Produktseite

MPC 710 D6 T40

150945

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
ERP conformity	Yes		
Certifications	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN710		DN
Rated voltage (entire device)	400	V	U _{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	10 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Steel		mat _{impeller}
Weight	250	kg	m
Nominal air flow rate, nominal point m³/h	12502.8	m³/h	q _{v,nom}
Nominal external pressure, static	519.9	Pa	p _{s,nom}
Fan type	Radial		Fan _{type}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	3.47	m³/s	q _{v,nom}
Actual electrical input power, nominal point	2.76	kW	P _{e,nom}
Face velocity, nominal point	7.9	m/s	v _{nom}
Nominal external pressure, static	519.9	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	65.7	%	η _{es,SUP}
Highest external air leakage rate	0.01	%	
Enclosure sound level, nominal point	76	dB(A)	L _{WA2}
Rating	Product is compliant 2018		


MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	2761	W	P _{ed, max}
Max. operating current (device)	7	A	I _{ed, max}
Max. speed	990	1/min	n _{max}
Max. stat. efficiency	60.7	%	η _{es}
Max. fan efficiency	66	%	η _e
Max. flowrate	19550	m³/h	q _{v, max}
Max. stat pressure	735	Pa	p _{sf, max}
Max. medium temperature	120	°C	T _{m, max}
Max. environment temperature	60	°C	T _{amb, max}
Min. environment temperature	-20	°C	T _{amb, min}



zur Produktseite


SCHALTPLÄNE / MASSZEICHNUNGEN



MPC 710 D6 T40

150945

ruck




zur Produktseite

MPC 710 D6 T40

150945

ruck




zur Produktseite

MPC 710 D6 T40

150945

ruck




zur Produktseite

MPC 710 D6 T40

150945

ruck



zur Produktseite

MECHANICAL ACCESSORIES

USM 1200 710 | 152657



- Transition spigot
- Galvanized steel sheet
- Insulated

USM 1200 630 | 152665



- Transition spigot
- Galvanized steel sheet
- Insulated

GR MPC 04 | 152696



- Base frame für MPC
- Galvanized steel sheet

RVK 710 | 153914



- Automatic tube shutter
- Sheet steel, powder coated
- For vertical installation
- Flange mounting

RVK H 710 | 154879



- Automatic tube shutter
- Sheet steel, powder coated
- For horizontal installation
- Flange mounting

UQR 1200 710 01 | 152628



- Transition duct/tube
- Galvanized steel sheet
- Incl. 4 cylinder cap screws (M8 x 16 mm), 4 serrated lock washers for nominal size M8

UQR 1200 630 01 | 152633



- Transition duct/tube
- Galvanized steel sheet
- Incl. 4 cylinder cap screws (M8 x 16 mm), 4 serrated lock washers for nominal size M8

AS MPC 710 | 152672



- Inlet spigot
- Galvanized steel sheet

RVS 710 | 154201




- Tube connection spigot
- Sheet steel, powder coated
- Suitable for outdoor installation
- Flange mounting

ESD 710 | 153939




- Inlet cone
- Steel sheet, powder coated
- Flange mounting

SGW 710 | 154056



- Protection grille, wide meshed
- Steel sheet, galvanized
- Flange mounting

SGE 710 | 154083



- Protection grille, narrow meshed
- Steel sheet, galvanized
- Flange mounting

WSG MPC 1200 | 152716



- Weather protection grille
- Galvanized steel sheet

RD MPC 1200 | 152745




- Rain cover for outdoor installation
- Galvanized steel sheet

FB 1200 | 160870



- Air filter box for panel filter
- For MPC box 1200
- For 1 or 2 filter (not included)
- Housing made of galvanized sheet steel

UCP 1200 | 152667



- Closed panel
- Galvanized steel sheet

MB MPC 04 | 152709

WSH MPC 04 | 152682

RAF 710 | 154024

RAS 710 | 154253



zur Produktseite



- Motor protection shield
- Sendzimir galvanized sheet



- Weather protection hood
- Galvanized steel sheet



- Round flange
- Sheet steel, powder coated



- Round spigot, flexible
- Galvanized steel sheet, plastic band (PES)
- Temperature resistant up to 75 °C
- Flange mounting

ELECTRICAL ACCESSORIES

GS 03 | 107633



- Device switch
- U_{max} = 400 V, I_{max} = 25 A
- Switching capacity 400 V 3~ = 5,5 kW
- Protection class IP 55

MS 04 | 140413



- Motor protection switch with Isolator switchfunktion
- I_{max} = 400 V, 50/60 Hz
- Max. 4 kW
- Protection class IP 55

MTP 20 | 128146



- Potentiometer 10 kΩ
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 kΩ
- Step 1 + 2 settable 10 % - 100 % V_{dc}
- Step 3 100 % V_{dc}
- Supply voltage +10 V_{dc}

MTP 40 | 147359



- Potentiometer 10 kΩ
- Connection in terminal box
- Max. ambient temperature 50 °C
- PU: 20 pieces

SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature 0...+50 °C
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

FU 55 10 | 150237



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Fire mode function (smoke extract fans)

FU 55 09 | 150236



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Protection class IP 20, for switch cabinet

MTP 50 | 153133



- Potentiometer with multifunction output
- 230 VAC ±10 % / 50-60 Hz
- Selectable output: 1-10 VDC / 2-20 mA / 10-100 % PWM
- Min. and max. output value adjustable



zur Produktseite