

MPC 450 D4 F4 TI 30


146696

- Backward curved radial impeller
- Linear air flow
- Sheet steel housing double-walled, 30 mm mineral wool
- IE3 motor outside the airflow, controllable
- Smoke extract fan F400, 200 °C continuous operation
- Housing bottom designed with integrated drain



MAP

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

MPC 450 D4 F4 TI 30

146696

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	-		DN
Rated voltage (entire device)	400	V	U _{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Steel		mat _{impeller}
Weight	83.86	kg	m
Nominal air flow rate, nominal point m³/h	4899.6	m³/h	q _{v,nom}
Nominal external pressure, static	400	Pa	p _{s,nom}
Fan type	Radial		F _{antype}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	1.36	m³/s	q _{v,nom}
Actual electrical input power, nominal point	1.19	kW	P _{e,nom}
Face velocity, nominal point	8.8	m/s	v _{nom}
Nominal external pressure, static	400	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	63.4	%	η _{es,SUP}
Highest external air leakage rate	0.04	%	
Enclosure sound level, nominal point	75	dB(A)	L _{WA2}
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	1213	W	P _{ed, max}
Max. operating current (device)	2.4	A	I _{ed, max}
Max. speed	1635	1/min	n _{max}
Max. stat. efficiency	50.4	%	η _{es}
Max. fan efficiency	51.4	%	η _e
Max. flowrate	6380	m³/h	q _{v, max}
Max. stat pressure	830	Pa	p _{sf, max}
Max. medium temperature	200	°C	T _{m, max}
Max. environment temperature	60	°C	T _{amb, max}
Min. environment temperature	-20	°C	T _{amb, min}



to the product detail page

MPC 450 D4 F4 TI 30

146696

ruck

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 3~		phase
Control type		frequency-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Protection class		IP55		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwrsupmotor
Number of poles (1)		4.000000		num polesw1
Connection	Δ			wiringw1
Connection (wiring 2)	Y			wiringw2
Rated voltage	230		V	Urated, f1
Rated voltage (wiring 2)	400		V	Urated, f2
Rated current	4.23		A	Irated, f1
Rated current (wiring 2)	2.45		A	Irated, f2
Shaft power	1100		W	Pout, f1
Shaft power (wiring 2)	1100		W	Pout, f2
Speed	1450		1/min	n1
Speed (wiring 2)	1450		1/min	n2
Starting current	7.6		A	Istart, f1
Starting current (wiring 2)	7.6		A	Istart, f2
Efficiency class	IE3			IEmotor
Min. temperature	-20		°C	Tmotor, min
UL-Certification motor		UL recognized		ULcert

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Maximum resistance temperature	400	°C	Tfire
Maximum resistance time	120.000000		tfire
Fire resistance class	F 400 (120)		Fclass
Snow load class	-		SLclass




MPC 450 D4 F4 TI 30

146696

ruck


CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



MPC 450 D4 F4 TI 30

146696


ruck



MPC 450 D4 F4 TI 30


146696

ruck



MPC 450 D4 F4 TI 30


146696



to the product detail page


MPC 450 D4 F4 TI 30

146696



MECHANICAL ACCESSORIES

UCPD 700 | 146790



- Panel
- With condensate drain
- Galvanized steel sheet



to the product detail page

MPC 450 D4 F4 TI 30

146696

ELECTRICAL ACCESSORIES

GS 03 | 107633



- Device switch
- $U_{max} = 400\text{ V}$, $I_{max} = 25\text{ A}$
- Switching capacity $400\text{ V } 3\sim = 5,5\text{ kW}$
- Protection class IP 55

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output $0-10\text{ V DC} + \text{FC enable} + \text{setpoint reached}$
- Pressure setting by means of decade switch

MTP 20 | 128146



- Potentiometer $10\text{ k}\Omega$
- Switching contact $1\text{ A}/250\text{ V AC} - 2,5\text{ A}/12\text{ V DC}$
- Max. ambient temperature $50\text{ }^{\circ}\text{C}$
- VDE

MS 02 | 140409



- Motor protection switch with Isolator switchfunction
- $I_{max} = 400\text{ V}$, $50/60\text{ Hz}$
- Max. $1,5\text{ kW}$
- Protection class IP 55

FU 15 12 | 141854



- Frequency converter IP66
- Supply voltage $230\text{ V } 1\sim 50/60\text{ Hz}$
- Output voltage $0 - 230\text{ V } 3\sim$
- Fire mode function (smoke extract fans)

FU 15 18 | 141876



- Frequency converter
- Supply voltage $400\text{ V } 3\sim 50/60\text{ Hz}$
- Output voltage $0 - 400\text{ V } 3\sim$
- Fire mode function (smoke extract fans)

MTP 30 | 143289



- Stepped potentiometer $10\text{ k}\Omega$
- Step 1 + 2 settable $10\% - 100\% \text{ Vdc}$
- Step 3 $100\% \text{ Vdc}$
- Supply voltage $+10\text{ Vdc}$

MTP 40 | 147359



- Potentiometer $10\text{ k}\Omega$
- Connection in terminal box
- Max. ambient temperature $50\text{ }^{\circ}\text{C}$
- PU: 20 pieces

SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature $0...+50\text{ }^{\circ}\text{C}$
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

MTP 50 | 153133



- Potentiometer with multifunction output
- $230\text{ VAC } \pm 10\% / 50-60\text{ Hz}$
- Selectable output: $1-10\text{ VDC} / 2-20\text{ mA} / 10-100\% \text{ PWM}$
- Min. and max. output value adjustable



to the product detail page