


MPC 560 D4 F4 T40


162944

- Backward curved radial impeller
- Variable discharge direction right / left / up
- Galvanized sheet steel housing, double-walled, 25 mm mineral wool
- IE3 motor outside airflow, frequency controllable
- Smoke extract fan F400, 200 °C continuous operation, dual-use
- Housing bottom designed with integrated drain



MAP

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

MPC 560 D4 F4 T40

162944

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN630		DN
Rated voltage (entire device)	400	V	U _{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Steel		mat _{impeller}
Weight	127	kg	m
Nominal air flow rate, nominal point m³/h	10508.4	m³/h	q _{v,nom}
Nominal external pressure, static	432	Pa	p _{s,nom}
Fan type	Radial		F _{antype}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	2.92	m³/s	q _{v,nom}
Actual electrical input power, nominal point	2.52	kW	P _{e,nom}
Face velocity, nominal point	4.96	m/s	v _{nom}
Nominal external pressure, static	432	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	63.3	%	η _{es,SUP}
Enclosure sound level, nominal point	79	dB(A)	L _{WA2}
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	2661	W	P _{ed, max}
Max. operating current (device)	5	A	I _{ed, max}
Max. speed	1470	1/min	n _{max}
Max. stat. efficiency	55.9	%	η _{es}
Max. fan efficiency	56.6	%	η _e
Max. flowrate	13060	m³/h	q _{v, max}
Max. stat pressure	1040	Pa	p _{sf, max}
Max. medium temperature	200	°C	T _{m, max}
Max. environment temperature	60	°C	T _{amb, max}
Min. environment temperature	-20	°C	T _{amb, min}



to the product detail page

MPC 560 D4 F4 T40

162944

ruck

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 3~		phase
Control type		frequency-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwrsupmotor
Number of poles (1)		4.000000		num polesw1
Connection	Δ	Y		wiringw1
Connection (wiring 2)	Y			wiringw2
Rated voltage	230	460	V	U _{rated, f1}
Rated voltage (wiring 2)	400		V	U _{rated, f2}
Rated current	8.03	4.01	A	I _{rated, f1}
Rated current (wiring 2)	4.62		A	I _{rated, f2}
Shaft power	2200	2200	W	P _{out, f1}
Shaft power (wiring 2)	2200		W	P _{out, f2}
Speed	1435	1745	1/min	n _{f1}
Speed (wiring 2)	1435		1/min	n _{f2}
Starting current	64.3	38.1	A	I _{start, f1}
Starting current (wiring 2)	37		A	I _{start, f2}
Efficiency	87	89.5	%	η _{m, f1}
Efficiency (wiring 2)	87		%	η _{m, f2}
Efficiency class	IE3	IE3		IE _{motor}
Min. temperature	-20	-20	°C	T _{motor, min}
Cos Phi	0.790000	0.770000		cos φ
UL-Certification motor		UL recognized		ULcert

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Maximum resistance temperature	400	°C	T _{fire}
Maximum resistance time	120.000000		t _{fire}
Fire resistance class	F 400 (120)		F _{class}
Snow load class	-		SL _{class}




to the product detail page

MPC 560 D4 F4 T40

162944

ruck


CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



MPC 560 D4 F4 T40

162944

ruck




to the product detail page

MPC 560 D4 F4 T40

162944


ruck



MPC 560 D4 F4 T40

162944

ruck




to the product detail page

MPC 560 D4 F4 T40

162944

ruck



MPC 560 D4 F4 T40

162944

MECHANICAL ACCESSORIES

GR MPC 03 | 123434



- Base frame für MPC
- Galvanized steel sheet

WSH MPC 03 | 123435



- Weather protection hood
- Galvanized steel sheet

UQR 900 560 01 | 139875



- Transition duct / tube
- Galvanized steel sheet
- Incl. 4 cylinder cap screws (M8 x 16 mm), 4 serrated lock washers for nominal size M8

UQR 900 630 01 | 139887



- Transition duct/tube
- Galvanized steel sheet
- Incl. 4 cylinder cap screws (M8 x 16 mm), 4 serrated lock washers for nominal size M8

USM 900 560 | 139997



- Transition spigot
- Galvanized steel sheet
- Insulated

USM 900 630 | 140061



- Transition spigot
- Galvanized steel sheet
- Insulated

RD MPC 900 | 140101



- Rain cover for outdoor installation
- Galvanized steel sheet

USM 900 500 | 140364



- Transition spigot
- Galvanized steel sheet
- Insulated

WSG MPC 900 | 140755



- Weather protection grille
- Galvanized steel sheet

AS MPC 500 | 140871



- Inlet spigot
- Galvanized steel sheet

AS MPC 560 | 140876




- Inlet spigot
- Galvanized steel sheet

AS MPC 630 | 140880



- Inlet spigot
- Galvanized steel sheet

UCP 900 | 142569




- Closed panel
- Galvanized steel sheet

RAF 500 | 154021




- Round flange
- Sheet steel, powder coated

SGW 500 | 154052



- Protection grille, wide meshed
- Steel sheet, galvanized
- Flange mounting

SGE 500 | 154076



- Protection grille, narrow meshed
- Steel sheet, galvanized
- Flange mounting

RVS 500 | 154193



- Tube connection spigot
- Sheet steel, powder coated

RAS 500 F4 | 154305



- Round spigot, flexible
- Galvanized steel sheet, silicone band

RVK 500 F4 | 154395



- Automatic tube shutter
- Sheet steel, powder coated

RVK H 500 F4 | 155670



- Automatic tube shutter
- Sheet steel, powder coated



to the product detail page

MPC 560 D4 F4 T40

162944

- Suitable for outdoor installation
- Flange mounting
- 400 °C/120 min. conf. DIN EN 12101-3
F400, 75 °C continuous operation
- Flange mounting
- For vertical installation
- Flange mounting
- For horizontal installation
- Flange mounting

ELECTRICAL ACCESSORIES

GS 03 | 107633



- Device switch
- Umax = 400 V, Imax = 25 A
- Switching capacity 400 V 3~ = 5,5 kW
- Protection class IP 55

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

MTP 20 | 128146



- Potentiometer 10 kΩ
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MS 03 | 140411



- Motor protection switch with Isolator switchfunktion
- Imax = 400 V, 50/60 Hz
- Max. 2.2 kW
- Protection class IP 55

FU 22 12 | 141856



- Frequency converter IP66
- Supply voltage 230 V 1~ 50/60 Hz
- Output voltage 0 - 230 V 3~
- Fire mode function (smoke extract fans)

FU 22 16 | 141878



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Fire mode function (smoke extract fans)

MTP 30 | 143289



- Stepped potentiometer 10 kΩ
- Step 1 + 2 settable 10 % - 100 % Vdc
- Step 3 100 % Vdc
- Supply voltage+10 Vdc

MTP 40 | 147359



- Potentiometer 10 kΩ
- Connection in terminal box
- Max. ambient temperature 50 °C
- PU: 20 pieces

SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature 0...+50 °C
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

MTP 50 | 153133



- Potentiometer with multifunction output
- 230 VAC ±10 % / 50-60 Hz
- Selectable output: 1-10 VDC / 2-20 mA / 10-100 % PWM
- Min. and max. output value adjustable



to the product detail page