

AL 1250 D6 01

162573


ruck

- Innovative, high-efficiency axial fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing weight optimized, powder coated
- Efficient IE3 motor, frequency controllable
- Conveyed medium temperature up to 60 °C in continuous operation
- Exceeds current ErP regulation by 15 - 20%



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



AL 1250 D6 01

162573

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		$W \times H_{duct}$
Pipe connection size (DN)	DN1250		DN
Rated voltage (entire device)	400	V	U_{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	32 A		fuse
Housing material	Steel		matcasing
Impeller material	Steel		matimpeller
IP-protection class (entire device)	IPX4		IPcompl
IP-Protection class (terminal box)	IP66		IPebox
Weight	280	kg	m
Fan type	Axial		Fan _{type}
Category / Installation situation	B		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. operating current (device)	25.94	A	$I_{ed, max}$
Max. speed	780	1/min	n_{max}
Max. stat. efficiency	53.2	%	η_{es}
Max. fan efficiency	68.1	%	η_e
Max. flowrate	79450	m ³ /h	$q_{v, max}$
Max. stat pressure	420	Pa	$p_{sf, max}$
Max. medium temperature	60	°C	$T_{m, max}$
Max. environment temperature	60	°C	$T_{amb, max}$
Min. environment temperature	-20	°C	$T_{amb, min}$



MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 3~		phase
Control type		frequency-controlled		ctrltype
Installation type		IRM (In)		install
Isolation class		ISO F		ISOclass
Protection class		IP55		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwsupmotor
Number of poles (1)		6.000000		num polesw1
Connection	Δ			wiringw1
Connection (wiring 2)	Y			wiringw2
Rated voltage	400		V	Urated, f1
Rated voltage (wiring 2)	690		V	Urated, f2
Rated current	22		A	Irated, f1
Rated current (wiring 2)	12.8		A	Irated, f2
Shaft power	11000		W	Pout, f1
Shaft power (wiring 2)	11000		W	Pout, f2
Speed	970		1/min	nf1
Speed (wiring 2)	970		1/min	nf2
Starting current	154		A	Istart, f1
Starting current (wiring 2)	89.3		A	Istart, f2
Efficiency	90.3		%	ηm, f1
Efficiency (wiring 2)	90.3		%	ηm, f2
Efficiency class	IE3			IEmotor
Min. temperature	-20		°C	Tmotor, min
Cos Phi	0.800000	0.000000		cos φ
UL-Certification motor		UL recognized		ULcert


ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	777	1/min	n _{opt}
Efficiency level	70.8	%	N
Efficiency category	total		cat _{efficiency}
Input power of the motor at the energy efficiency optimum	10.92	kW	P _{e, opt}
Overall efficiency	70.9	%	η _{ges}
Measurement category	B		meas cat
Fan pressure at energy efficiency optimum	432	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	62035	m³/h	Q _{v, opt}



to the product detail page


CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



AL 1250 D6 01


162573

ruck




AL 1250 D6 01

162573



AL 1250 D6 01


162573



to the product detail page

AL 1250 D6 01

162573



MECHANICAL ACCESSORIES

RVS 1250-01 | 157482



- Tube connection spigot
- Sheet steel, powder coated
- Suitable for outdoor installation
- Flange mounting

ESD 1250 | 157580




- Inlet cone
- Steel sheet, powder coated
- Flange mounting

FAL 1250 | 157901




- Mounting foot
- Sheet steel, powder coated
- Flange mounting

SGW 1250 | 159544




- Protection grille, wide meshed
- Steel sheet, galvanized
- Flange mounting

SGW 1400 | 160421



- Protection grille, wide meshed
- Steel sheet, galvanized
- Flange mounting

SGE 1250 | 159520



- Protection grille, narrow meshed
- Steel sheet, galvanized
- Flange mounting

FSD 08 | 162473



- Set of 4 vibration dampers
- Made of natural rubber, hardness 55 Shore A

RAF 1250 | 157503



- Round flange
- Sheet steel, powder coated

RAS 1250 | 157645




- Round spigot, flexible
- Galvanized steel sheet, plastic band (PES)
- Temperature resistant up to 75 °C
- Flange mounting

FSD 11 | 162489



- Set of 4 vibration dampers
- All metal design, galvanized

TRA 1120-1250 | 163013



- Crossbeam
- Connection between mounting feet
- Galvanized steel sheet

RVK 1250 | 157847



- Automatic tube shutter
- Sheet steel, powder coated
- For vertical installation
- Flange mounting

RVK H 1250 | 164022



- Automatic tube shutter
- Sheet steel, powder coated
- For horizontal installation
- Flange mounting

MR 1250 | 166134



- Mounting ring
- For vertical mounting
- Powder-coated sheet steel
- Flange mounting DN 1250



ELECTRICAL ACCESSORIES

MS 07 | 160185



- Motor protection switch with device switch function
- For three phase motors
- I_{max} = 25 A

MTP 20 | 128146



- Potentiometer 10 kΩ
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 kΩ
- Step 1 + 2 settable 10 % - 100 % V_{dc}
- Step 3 100 % V_{dc}
- Supply voltage +10 V_{dc}

SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature 0...+50 °C
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

FU 110 14 | 161415



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Fire mode function (smoke extract fans)

FU 110 13 | 161414



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Protection class IP 20, for switch cabinet



to the product detail page