

# AL 800 D4 F4 04

162523


ruck

- Innovative, high-efficiency axial fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing weight optimized, powder coated
- Efficient IE3 motor, frequency controllable
- Smoke extract fan F400, 60 °C continuous operation, dual-use
- Exceeds current ErP regulation



## FAN CURVES

| Name        | Value | Unit |
|-------------|-------|------|
| Volume flow | 0     | m³/h |
| Pressure    | 0     | Pa   |



to the product detail page

## GENERAL DATA

| Name                                  | Value    | Unit | Formula symbol      |
|---------------------------------------|----------|------|---------------------|
| Labeling                              | CE, UKCA |      |                     |
| Duct size                             | -        |      | $W \times H_{duct}$ |
| Pipe connection size (DN)             | DN800    |      | DN                  |
| Rated voltage (entire device)         | 400      | V    | $U_{rated}$         |
| Phases (entire device)                | 3~       |      | phase               |
| Electrical protection (entire device) | 10 A     |      | fuse                |
| Housing material                      | Steel    |      | matcasing           |
| Impeller material                     | Steel    |      | matimpeller         |
| IP-protection class (entire device)   | IPX4     |      | IPcompl             |
| IP-Protection class (terminal box)    | IP55     |      | IPebox              |
| Weight                                | 145.1    | kg   | m                   |
| Fan type                              | Axial    |      | Fan <sub>type</sub> |
| Category / Installation situation     | B        |      | cat                 |

## MAXIMAL DATA

| Name                            | Value | Unit              | Formula symbol |
|---------------------------------|-------|-------------------|----------------|
| Max. power consumption (device) | 4780  | W                 | $P_{ed, max}$  |
| Max. operating current (device) | 9.92  | A                 | $I_{ed, max}$  |
| Max. speed                      | 1180  | 1/min             | $n_{max}$      |
| Max. stat. efficiency           | 55.7  | %                 | $\eta_{es}$    |
| Max. fan efficiency             | 71.1  | %                 | $\eta_e$       |
| Max. flowrate                   | 31640 | m <sup>3</sup> /h | $Q_{v, max}$   |
| Max. stat pressure              | 780   | Pa                | $p_{sf, max}$  |
| Max. medium temperature         | 60    | °C                | $T_{m, max}$   |
| Max. environment temperature    | 60    | °C                | $T_{amb, max}$ |
| Min. environment temperature    | -20   | °C                | $T_{amb, min}$ |



MOTOR DATA

| Name                        | Value    |                      | Unit  | Formula symbol           |
|-----------------------------|----------|----------------------|-------|--------------------------|
|                             | 50 Hz    | 60 Hz                |       |                          |
| Rated frequency (device)    |          | 50                   |       | f                        |
| Motor type                  |          | AC 3~                |       | phase                    |
| Control type                |          | frequency-controlled |       | ctrltype                 |
| Installation type           |          | IRM (In)             |       | install                  |
| Isolation class             |          | ISO H                |       | ISOclass                 |
| Protection class            |          | IP55                 |       | IPmotor                  |
| Is pole-changeable          |          | No                   |       | polexch                  |
| Type of power supply        |          | AC 3~                |       | pwsupmotor               |
| Number of poles (1)         |          | 4.000000             |       | num polesw1              |
| Connection                  | Δ        |                      |       | wiringw1                 |
| Connection (wiring 2)       | Y        |                      |       | wiringw2                 |
| Rated voltage               | 400      |                      | V     | Urated, f1               |
| Rated voltage (wiring 2)    | 690      |                      | V     | Urated, f2               |
| Rated current               | 10.4     |                      | A     | Irated, f1               |
| Rated current (wiring 2)    | 6.03     |                      | A     | Irated, f2               |
| Shaft power                 | 5500     |                      | W     | Pout, f1                 |
| Shaft power (wiring 2)      | 5500     |                      | W     | Pout, f2                 |
| Speed                       | 1465     |                      | 1/min | n <sub>f1</sub>          |
| Speed (wiring 2)            | 1465     |                      | 1/min | n <sub>f2</sub>          |
| Starting current            | 86.3     |                      | A     | Istart, f1               |
| Starting current (wiring 2) | 50       |                      | A     | Istart, f2               |
| Efficiency                  | 89.7     |                      | %     | η <sub>m</sub> , f1      |
| Efficiency (wiring 2)       | 89.7     |                      | %     | η <sub>m</sub> , f2      |
| Efficiency class            | IE3      |                      |       | IE <sub>motor</sub>      |
| Min. temperature            | -20      |                      | °C    | T <sub>motor</sub> , min |
| Cos Phi                     | 0.850000 | 0.000000             |       | cos φ                    |
| UL-Certification motor      |          | None                 |       | ULcert                   |

ERP DATA (LOT11)

| Name                                                      | Value | Unit  | Formula symbol            |
|-----------------------------------------------------------|-------|-------|---------------------------|
| Speed at the energy efficiency optimum                    | 1168  | 1/min | n <sub>opt</sub>          |
| Efficiency level                                          | 74.3  | %     | N                         |
| Efficiency category                                       | total |       | cat <sub>efficiency</sub> |
| Input power of the motor at the energy efficiency optimum | 3.93  | kW    | P <sub>e</sub> , opt      |
| Overall efficiency                                        | 76.9  | %     | η <sub>ges</sub>          |
| Measurement category                                      | B     |       | meas cat                  |
| Fan pressure at energy efficiency optimum                 | 415   | Pa    | p <sub>f</sub> , opt      |
| Flowrate at energy efficiency optimum                     | 24188 | m³/h  | Q <sub>v</sub> , opt      |




to the product detail page

SMOKE EXTRACT DATA

| Name                           | Value       | Unit | Formula symbol      |
|--------------------------------|-------------|------|---------------------|
| Maximum resistance temperature | 400         | °C   | T <sub>fire</sub>   |
| Maximum resistance time        | 120.000000  |      | t <sub>fire</sub>   |
| Fire resistance class          | F 400 (120) |      | F <sub>class</sub>  |
| Snow load class                | -           |      | SL <sub>class</sub> |


## CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



# AL 800 D4 F4 04


162523

ruck



AL 800 D4 F4 04


162523




to the product detail page

AL 800 D4 F4 04


162523





## MECHANICAL ACCESSORIES

**SGW 800 | 154057**



- Protection grille, wide meshed
- Steel sheet, galvanized
- Flange mounting

**RAF 800 | 157395**



- Round flange
- Sheet steel, powder coated

**RVS 800-01 | 157478**



- Tube connection spigot
- Sheet steel, powder coated
- Suitable for outdoor installation
- Flange mounting

**ESD 800 | 157527**



- Inlet cone
- Steel sheet, powder coated
- Flange mounting

**RAS 800 F4 | 157690**



- Round spigot, flexible
- Galvanized steel sheet, silicone band
- 400 °C/120 min. conf. DIN EN 12101-3
- F400, 75 °C continuous operation
- Flange mounting

**RVK 800 F4 | 157738**



- Automatic tube shutter
- Sheet steel, powder coated
- For vertical installation
- Flange mounting

**FAL 800 | 157897**




- Mounting foot
- Sheet steel, powder coated
- Flange mounting

**RVK H 800 F4 | 159425**




- Automatic tube shutter
- Sheet steel, powder coated
- For horizontal installation
- Flange mounting

**SGE 800 | 159516**



- Protection grille, narrow meshed
- Steel sheet, galvanized
- Flange mounting

**SGW 900 | 159541**



- Protection grille, wide meshed
- Steel sheet, galvanized
- Flange mounting

**FSD10 | 162484**



- Set of 4 vibration dampers
- All metal design, galvanized



to the product detail page

## ELECTRICAL ACCESSORIES

### CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

### MTP 20 | 128146



- Potentiometer 10 k $\Omega$
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

### MTP 30 | 143289



- Stepped potentiometer 10 k $\Omega$
- Step 1 + 2 settable 10 % - 100 % Vdc
- Step 3 100 % Vdc
- Supply voltage+10 Vdc

### SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature 0...+50 °C
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

### FU 55 23 | 161385



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Fire mode function (smoke extract fans)



to the product detail page