

DVNI 400 EC 30

145178


ruck

- Backward curved radial impeller
- Vertical discharge
- Housing: insulated, AlMg3, hinged, grease drain
- High efficiency EC motor, steplessly controllable
- For greasy kitchen exhaust air, up to 120 °C
- Integrated device switch



MAP

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

DVNI 400 EC 30

145178

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN400		DN
Rated voltage (entire device)	230	V	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	10 A		fuse
Housing material	Aluminium		mat _{casing}
Impeller material	Steel		mat _{impeller}
Weight	62.8	kg	m
Nominal air flow rate, nominal point m³/h	3236.4	m³/h	q _{v,nom}
Nominal external pressure, static	772.7	Pa	p _{s,nom}
Fan type	Radial		F _{an} type
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	0.9	m³/s	q _{v,nom}
Actual electrical input power, nominal point	1.18	kW	P _{e,nom}
Face velocity, nominal point	4.4	m/s	v _{nom}
Nominal external pressure, static	772.7	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	68.3	%	η _{es,SUP}
Enclosure sound level, nominal point	87	dB(A)	L _{WA2}
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	1196	1196	W	P _{ed, max}
Max. operating current (device)	8.8	8.8	A	I _{ed, max}
Max. speed	2000	2000	1/min	n _{max}
Max. stat. efficiency	55.8	55.8	%	η _{es}
Max. fan efficiency	56.6	56.6	%	η _e
Max. flowrate	5640	5640	m³/h	q _{v, max}
Max. stat pressure	950	950	Pa	p _{sf, max}
Max. medium temperature	120	120	°C	T _{m, max}
Max. environment temperature	50	50	°C	T _{amb, max}
Min. environment temperature	-20	-20	°C	T _{amb, min}



to the product detail page

DVNI 400 EC 30

145178




MOTOR DATA


Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Protection class		IP54		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrSupmotor
Rated voltage	230		V	Urated, f1
Rated current	8		A	Irated, f1
Shaft power	1100		W	Pout, f1
Speed	2100		1/min	nf1
UL-Certification motor		None		ULcert



to the product detail page

CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS






DVNI 400 EC 30

145178

ruck



145178 01




to the product detail page

DVNI 400 EC 30

145178


ruck



145178 01



to the product detail page



MECHANICAL ACCESSORIES

DVK 400 10 | 152897



- Automatic roof shutter
- Galvanized steel sheet

DAF 400 | 109826




- Roof inlet flange
- Galvanized steel sheet

DSF 355-10 | 126160



- Flat roof socket
- Made of aluminum AlMg3
- Sound and heat insulation

DAP 450 | 133976



- Adapter plate for roof mounting of roof fans
- Galvanized steel sheet

DSS 355-10 | 126403




- Flat roof socket silencer
- Made of aluminum AlMg3
- Sound and heat insulation

DSS 355-12 | 134395



- Sloped roof socket silencer
- Made of aluminum AlMg3
- Sound and heat insulation
- For roof slope 3°

DAS 400 F4 | 150093



- Flexible roof inlet spigot F4
- Temperature resistant up to 400 °C

DSF 355-12 | 133793



- Sloped roof socket
- Made of aluminum AlMg3
- Sound and heat insulation
- For roof slope 3°



to the product detail page

ELECTRICAL ACCESSORIES

MTP 20 | 128146



- Potentiometer 10 kΩ
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 kΩ
- Step 1 + 2 settable 10 % - 100 % Vdc
- Step 3 100 % Vdc
- Supply voltage +10 Vdc

MTP 40 | 147359



- Potentiometer 10 kΩ
- Connection in terminal box
- Max. ambient temperature 50 °C
- PU: 20 pieces

SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature 0...+50 °C
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

SEN P1000 | 126080



- Differential pressure sensor
- P-control, PV-control
- P = 2 pcs. required, PV = 1 pcs. required

MTP 50 | 153133



- Potentiometer with multifunction output
- 230 VAC ±10 % / 50-60 Hz
- Selectable output: 1-10 VDC / 2-20 mA / 10-100 % PWM
- Min. and max. output value adjustable

