

DVNI 630 D4 30

145044


ruck

- Backward curved radial impeller
- Vertical discharge
- Housing: insulated, AlMg3, hinged, grease drain
- Efficient IE3 motor, frequency controllable
- For greasy kitchen exhaust air, up to 120 °C
- Integrated device switch



MAP

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

DVNI 630 D4 30

145044

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN560		DN
Rated voltage (entire device)	400	V	U _{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	10 A		fuse
Housing material	Aluminium		mat _{casing}
Impeller material	Steel		mat _{impeller}
Weight	180	kg	m
Nominal air flow rate, nominal point m³/h	10040.4	m³/h	q _{v,nom}
Nominal external pressure, static	786	Pa	p _{s,nom}
Fan type	Radial		Fan _{type}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	2.79	m³/s	q _{v,nom}
Actual electrical input power, nominal point	4.12	kW	P _{e,nom}
Face velocity, nominal point	5.7	m/s	v _{nom}
Nominal external pressure, static	786	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	66.6	%	η _{es,SUP}
Enclosure sound level, nominal point	94	dB(A)	L _{WA2}
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	4115	W	P _{ed, max}
Max. operating current (device)	8.5	A	I _{ed, max}
Max. speed	1490	1/min	n _{max}
Max. stat. efficiency	54	%	η _{es}
Max. fan efficiency	54.9	%	η _e
Max. flowrate	14350	m³/h	q _{v, max}
Max. stat pressure	1300	Pa	p _{sf, max}
Max. medium temperature	120	°C	T _{m, max}
Max. environment temperature	50	°C	T _{amb, max}
Min. environment temperature	-20	°C	T _{amb, min}



to the product detail page


MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 3~		phase
Control type		frequency-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Protection class		IP55		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwrsupmotor
Number of poles (1)		4.000000		num polesw1
Connection	Δ	Y		wiringw1
Connection (wiring 2)	Y			wiringw2
Rated voltage	230	460	V	U _{rated, f1}
Rated voltage (wiring 2)	400		V	U _{rated, f2}
Rated current	14.3	7.28	A	I _{rated, f1}
Rated current (wiring 2)	8.2		A	I _{rated, f2}
Shaft power	4000	4000	W	P _{out, f1}
Shaft power (wiring 2)	4000		W	P _{out, f2}
Speed	1450	1755	1/min	n _{f1}
Speed (wiring 2)	1450		1/min	n _{f2}
Starting current	100	58.2	A	I _{start, f1}
Starting current (wiring 2)	57.4		A	I _{start, f2}
Efficiency	89.1	89.5	%	$\eta_m, f1$
Efficiency (wiring 2)	89.1		%	$\eta_m, f2$
Efficiency class	IE3	IE3		IE _{motor}
Min. temperature	-20	-20	°C	T _{motor, min}
Cos Phi	0.790000	0.770000		cos φ
UL-Certification motor		UL recognized		ULcert



to the product detail page


CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS




DVNI 630 D4 30

145044

ruck



to the product detail page




145044 01



DVNI 630 D4 30

145044

ruck



145044 01




to the product detail page

DVNI 630 D4 30

145044

ruck



MECHANICAL ACCESSORIES

DAF 560 | 122288



- Roof inlet flange
- Galvanized steel sheet

DSS 560-10 | 126471




- Flat roof socket silencer
- Made of aluminum AlMg3
- Sound and heat insulation

DSS 560-12 | 134486



- Sloped roof socket silencer
- Made of aluminum AlMg3
- Sound and heat insulation
- For roof slope 3°

DAS 560 F4 | 150095



- Flexible roof inlet spigot F4
- Temperature resistant up to 400 °C

DSF 560-12 | 133892



- Sloped roof socket
- Made of aluminum AlMg3
- Sound and heat insulation
- For roof slope 3°

DVK 560 10 | 152898



- Automatic roof shutter
- Galvanized steel sheet

DAP 560 | 133979



- Adapter plate for roof mounting of fans
- Galvanized steel sheet

DSF 560-10 | 126237



- Flat roof socket
- Made of aluminum AlMg3
- Sound and heat insulation



to the product detail page

ELECTRICAL ACCESSORIES

MS 04 | 140413



- Motor protection switch with Isolator switchfunktion
- I_{max} = 400 V, 50/60 Hz
- Max. 4 kW
- Protection class IP 55

MTP 20 | 128146



- Potentiometer 10 kΩ
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 kΩ
- Step 1 + 2 settable 10 % - 100 % Vdc
- Step 3 100 % Vdc
- Supply voltage +10 Vdc

MTP 40 | 147359



- Potentiometer 10 kΩ
- Connection in terminal box
- Max. ambient temperature 50 °C
- PU: 20 pieces

SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature 0...+50 °C
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

FU 55 06 | 141879



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Fire mode function (smoke extract fans)

FU 55 05 | 141868



- Frequency converter
- Supply voltage 400 V 3~ 50/60 Hz
- Output voltage 0 - 400 V 3~
- Protection class IP 20, for switch cabinet

MTP 50 | 153133



- Potentiometer with multifunction output
- 230 VAC ±10 % / 50-60 Hz
- Selectable output: 1-10 VDC / 2-20 mA / 10-100 % PWM
- Min. and max. output value adjustable



to the product detail page