

iPAC Industrial Air Conditioning

Model : iPAC-40

The Brand New iPAC range of stand-alone, light industrial portable air conditioning units are a great option for a flexible cooling and heating solution with WIFI control. The iPAC Industrial Portable Air Conditioning Units come complete with Cooling, Heating and Dehumidifying functions for all year-round use.

Features

- Auto Restart after Power Outage
- Automatic Self Evaporating System
- Auto-Stop when Water Tank Full
- 3 Fan Speeds for Cooling
- Designed to Run Continuously
- LED Remote Control
- WIFI Control with SmartLife App
- Daily or Weekly On/Off Timers



Specifications



Model	iKOOL-iPAC-40
EAN Barcode	5060974530410
Power Rating	1/200-240V/50Hz
Refrigerant	R290
Capacity BTU/h (Cooling)	14000 / 4
Capacity BTU/h (Heating)	14000 / 4
Power Input (W) Cooling~Heating	1535 ~ 1290
Current Input (A) Cooling~Heating	6.4 ~ 5.4
Moisture Removed L/24h	70 L/24
Maximum Power Consumption	1700 W
Max Room Size (m2)	40 m2
Max Conservatory Size (m2)	20 m2
Selectable Temp Range	17-30 / 15-25
Indoor Noise Level	58/60/65
Indoor Airflow	450 m3/h
Max. Current Rating (A) Fuse Rating	16.5
Airflow Distance	8 m
Unit Dimensions	300mm x 505mm x 778mm
Packaged Unit Dimensions	370mm x 590mm x 835mm
Net Weight	32.4 Kg
Packaged Weight	34.5 Kg
Timer Setting	0-24 Hrs
Exhaust Hose Length	1.5m
Exhaust Hose Diameter	150mm
Window Extraction Kit	YES
Min/Max Operating Temp	-15 C
Automatic Restart After Power Failure	YES
Quiet Operation	YES
Auto Operation	YES

All ACC Product's are Guaranteed for 12 Months (Unless Otherwise Stated) from the Date of Original Purchase.



airconditioningcentre®

Copyright 2002 - 2023 Air Conditioning Centre / Martin Industries
Air Conditioning Centre is a Registered Trademark of Martin Industries Ltd. E&OE. Registered in England & Wales Co. No. 05436428

Martin Industries Ltd
Unit 8
Milton Business Centre
Wick Drive
New Milton
Hampshire
BH25 6RH
United Kingdom

Telephone: 0370 33 44 55 6

Email: info@airconditioningcentre.com

Website: www.airconditioningcentre.com